



# ADJUSTABLE APRON ASSEMBLY HANGER Nº53K

COPYRIGHT

FOR DOOR THICKNESS 38 (1½") TO 48 (1⅞")  
MAX. DOOR WEIGHT 150kg (330lb)

## HANGER ASSEMBLY

1. ASSEMBLE HANGER BODY ONTO APRON BY SCREWING PENDANT INTO ADJUSTMENT NUT.
2. DRILL HOLES FOR PENDANTS 11 (7/16") DIA. - POSITIONED 48 (1⅞") MIN. FROM EDGE AND \*21 (13/16") FROM SIDE OF DOOR NEAREST LINTOL. COUNTER BORE HOLE TO DEPTH OF 5 (3/16") AT 22 (7/8") DIA. \*SEE NOTE BELOW FOR DOUBLE DOORS.
3. WITH APRONS ADJUSTED TO DOOR THICKNESS TIGHTEN APRON NUTS AND POSITION PENDANT OVER HOLES.
4. SECURE APRONS WITH WOODSCREWS PROVIDED. DOOR IS NOW READY FOR INSTALLATION.

### IMPORTANT

THE FIXED PLATE OF THE ADJUSTABLE APRONS MUST ALWAYS BE POSITIONED ON THE SIDE OF THE DOOR NEAREST TO THE LINTOL.

WHEN SOFFIT FIXING IS USED THE FIXED PLATES MUST ALWAYS BE POSITIONED ON THE SAME SIDE.

### NOTE FOR DOUBLE RUN DOORS

HANGER APRONS MUST BE FIXED FLUSH WITH DOOR FACES ON DOORS 44 (1¾") TO 48 (1⅞") THICK. DIMENSION \*21 (13/16") WILL BE INCREASED ACCORDINGLY.

